

PEA-RP100/125/140GAA and PEA-RP170WJA

OUTDOOR:PUHZ-RP·KA2

<Heating Capacity>

Model Name	Capacity	Input	Indoor intake air DB C	Outdoor intake air WB C											
				-10		-5		0		5		10		15	
				CA	P.C.	CA	P.C.	CA	P.C.	CA	P.C.	CA	P.C.	CA	P.C.
PEA-RP100GAA	11200	2.51	15	7112	1.48	7728	1.63	8624	1.88	11312	2.26	12768	2.51	14224	2.71
			20	6832	1.61	7392	1.76	8176	2.03	10920	2.43	12320	2.71	13720	2.91
			25	6608	1.71	7168	1.91	7840	2.21	10304	2.59	11872	2.90	13216	3.12
PEA-RP125GAA	14000	3.27	15	8890	1.93	9660	2.13	10780	2.45	14140	2.94	15960	3.27	17780	3.53
			20	8540	2.09	9240	2.29	10220	2.65	13650	3.17	15400	3.53	17150	3.79
			25	8260	2.22	8960	2.49	9800	2.88	12880	3.37	14840	3.78	16520	4.07
PEA-RP140GAA	16000	3.90	15	10160	2.30	11040	2.54	12320	2.93	16160	3.51	18240	3.90	20320	4.21
			20	9760	2.50	10560	2.73	11680	3.16	15600	3.78	17600	4.21	19600	4.52
			25	9440	2.65	10240	2.96	11200	3.43	14720	4.02	16960	4.50	18880	4.86
PEA-RP170WJA	20000	6.00	15	12700	3.54	13800	3.90	15400	4.50	20200	5.40	22800	6.00	25400	6.48
			20	12200	3.84	13200	4.20	14600	4.86	19500	5.82	22000	6.48	24500	6.96
			25	11800	4.08	12800	4.56	14000	5.28	18400	6.18	21200	6.93	23600	7.47