

1. SPECIFICATIONS

Floor standing (Concealed type)

Model				PFFY-W20VCM-A	PFFY-W25VCM-A	PFFY-W32VCM-A	PFFY-W40VCM-A	
Power source				1-phase 220-230-240 V 50/60 Hz	1-phase 220-230-240 V 50/60 Hz	1-phase 220-230-240 V 50/60 Hz	1-phase 220-230-240 V 50/60 Hz	
Cooling capacity (Nominal)	*1	kW		2.2	2.8	3.6	4.5	
	*1	BTU/h		7,500	9,600	12,300	15,400	
(220V)	*2	Power input		0.022	0.029	0.035	0.038	
	*2	Current input		A	0.33	0.38	0.38	
Heating capacity (Nominal)	*3	kW		2.5	3.2	4.0	5.0	
	*3	BTU/h		8,500	10,900	13,600	17,100	
(220V)	*2	Power input		0.022	0.029	0.035	0.038	
	*2	Current input		A	0.33	0.38	0.38	
External finish				Galvanized steel plate	Galvanized steel plate	Galvanized steel plate	Galvanized steel plate	
External dimension H × W × D		*4	mm	615 (690) x 700 x 200	615 (690) x 700 x 200	615 (690) x 700 x 200	615 (690) x 900 x 200	
		*4	in.	24-1/4 (27-3/16) x 27-9/16 x 7-7/8	24-1/4 (27-3/16) x 27-9/16 x 7-7/8	24-1/4 (27-3/16) x 27-9/16 x 7-7/8	24-1/4 (27-3/16) x 35-7/16 x 7-7/8	
Net weight			kg (lbs)	18.5 (42)	18.5 (42)	19 (42)	23 (51)	
Heat exchanger				Cross fin (Aluminum fin and copper tube)	Cross fin (Aluminum fin and copper tube)	Cross fin (Aluminum fin and copper tube)	Cross fin (Aluminum fin and copper tube)	
				Water Volume	L	0.8	0.8	1.0
FAN	*5	Type × Quantity		Sirocco fan x 2	Sirocco fan x 2	Sirocco fan x 2	Sirocco fan x 3	
		External static press.	Pa	<0> - 10 - <40> - <60>	<0> - 10 - <40> - <60>	<0> - 10 - <40> - <60>	<0> - 10 - <40> - <60>	
			mmH ₂ O	<0.0> - 1.0 - <4.1> - <6.1>	<0.0> - 1.0 - <4.1> - <6.1>	<0.0> - 1.0 - <4.1> - <6.1>	<0.0> - 1.0 - <4.1> - <6.1>	
		Motor Type		DC motor	DC motor	DC motor	DC motor	
		Motor output		kW	0.096	0.096	0.096	0.096
		Driving mechanism		Direct-driven by motor	Direct-driven by motor	Direct-driven by motor	Direct-driven by motor	
	Air flow rate			(Low-Mid-High)	(Low-Mid-High)	(Low-Mid-High)	(Low-Mid-High)	
		m ³ /min	5.0 - 6.0 - 7.0	5.5 - 7.0 - 8.5	6.5 - 7.5 - 9.0	8.0 - 9.5 - 11.0		
			L/s	83 - 100 - 117	92 - 117 - 142	108 - 125 - 150	133 - 158 - 183	
			cfm	177 - 212 - 247	194 - 247 - 300	230 - 265 - 318	282 - 335 - 388	
Sound pressure level (measured in anechoic room)				(Low-Mid-High)	(Low-Mid-High)	(Low-Mid-High)	(Low-Mid-High)	
				*2 dB <A>	21.0-23.0-26.0	22.0-26.0-30.0	25.0-28.0-32.0	25.0-27.0-30.0
Insulation material				Polystyrene foam, Polyethylene foam, Urethane foam	Polystyrene foam, Polyethylene foam, Urethane foam	Polystyrene foam, Polyethylene foam, Urethane foam	Polystyrene foam, Polyethylene foam, Urethane foam	
Air filter				PP honeycomb fabric.	PP honeycomb fabric.	PP honeycomb fabric.	PP honeycomb fabric.	
Protection device				Fuse	Fuse	Fuse	Fuse	
Refrigerant control device				Flow control valve	Flow control valve	Flow control valve	Flow control valve	
Connectable HBC/Hydro unit				CMB-WM-V-AA, CMB-WM-F-AA, CMB-WM-V-BB/CMH-WM-V-A	CMB-WM-V-AA, CMB-WM-F-AA, CMB-WM-V-BB/CMH-WM-V-A	CMB-WM-V-AA, CMB-WM-F-AA, CMB-WM-V-BB/CMH-WM-V-A	CMB-WM-V-AA, CMB-WM-F-AA, CMB-WM-V-BB/CMH-WM-V-A	
Water piping diameter				*6, 7				
	Connection size	Inlet	mm O.D.	22	22	22	22	
		Outlet	mm O.D.	22	22	22	22	
	Field pipe size	Inlet	mm I.D.	20	20	20	20	
		Outlet	mm I.D.	20	20	20	20	
Field drain pipe size			mm (in.)	O.D.32 (1-1/4)	O.D.32 (1-1/4)	O.D.32 (1-1/4)	O.D.32 (1-1/4)	
Drawing	External			KL94T470, KL94R952	KL94T470, KL94R952	KL94T470, KL94R952	KL94T470, KL94R952	
	Wiring			KL94R951	KL94R951	KL94R951	KL94R951	
	Refrigerant cycle			-	-	-	-	
Standard attachment	Document			Installation Manual, Instruction Book	Installation Manual, Instruction Book	Installation Manual, Instruction Book	Installation Manual, Instruction Book	
	Accessory			Washer, Drain hose, Tie band, Leg, Screw	Washer, Drain hose, Tie band, Leg, Screw	Washer, Drain hose, Tie band, Leg, Screw	Washer, Drain hose, Tie band, Leg, Screw	
Remarks				* Details on foundation work, duct work, insulation work, electrical wiring, power source switch, and other items shall be referred to the Installation Manual. * Due to continuing improvement, above specifications may be subject to change without notice.				

Notes:		Unit converter
1.Nominal cooling conditions Indoor: 27°CDB./19°CWB. (81°FDB./66°FWB.), Outdoor: 35°CDB. (95°FDB.) Pipe length: 7.5 m (24-9/16 ft.), Level difference: 0 m (0 ft.)		BTU/h =kW x 3,412
2.The values are measured at the factory setting of external static pressure.		cfm =m ³ /min x 35.31
3.Nominal heating conditions Indoor: 20°CDB. (68°FDB.), Outdoor: 7°CDB./6°CWB. (45°FDB./43°FWB.) Pipe length: 7.5 m (24-9/16 ft.), Level difference: 0 m (0 ft.)		lbs =kg/0.4536
4.The values in () show the height of unit with leg.		
5.The factory setting of external static pressure is shown without < >. Refer to "Fan characteristics curves", according to the external static pressure, in DATA BOOK for the usable range of air flow rate.		
6.Be sure to install a valve on the water inlet/outlet.		
7.Install a strainer (40 mesh or more) on the pipe next to the valve to remove the foreign matters.		
8.Please group units that operate on 1 branch of HBC.		
		*Above specification data is subject to rounding variation.

1. SPECIFICATIONS

Floor standing (Concealed type)

Model			PFFY-W50VCM-A				
Power source			1-phase 220-230-240 V 50/60 Hz				
Cooling capacity (Nominal)	*1	kW	5.6				
	*1	BTU/h	19,100				
(220V)	*2	Power input	kW	0.062			
	*2	Current input	A	0.52			
Heating capacity (Nominal)	*3	kW	6.3				
	*3	BTU/h	21,500				
(220V)	*2	Power input	kW	0.062			
	*2	Current input	A	0.52			
External finish			Galvanized steel plate				
External dimension H × W × D	*4	mm	615 (690) x 900 x 200				
	*4	in.	24-1/4 (27-3/16) x 35-7/16 x 7-7/8				
Net weight		kg (lbs)	23 (51)				
Heat exchanger			Cross fin (Aluminum fin and copper tube)				
	Water Volume		L	1.3			
FAN	Type × Quantity		Sirocco fan x 3				
	*5	External static press.	Pa	<0> - 10 - <40> - <60>			
			mmH ₂ O	<0.0> - 1.0 - <4.1> - <6.1>			
	Motor Type		DC motor				
	Motor output		kW	0.096			
	Driving mechanism		Direct-driven by motor				
	Air flow rate		(Low-Mid-High)				
		m ³ /min	10.5 - 12.5 - 14.5				
		L/s	175 - 208 - 242				
		cfm	371 - 441 - 512				
Sound pressure level (measured in anechoic room)			(Low-Mid-High)				
	*2	dB <A>	28.0-32.0-35.0				
Insulation material			Polystyrene foam, Polyethylene foam, Urethane foam				
Air filter			PP honeycomb fabric.				
Protection device			Fuse				
Refrigerant control device			Flow control valve				
Connectable HBC/Hydro unit			CMB-WM-V-AA, CMB-WM-F-AA, CMB-WM-V-BB/CMH-WM-V-A				
Water piping diameter			*6, 7				
	Connection size	Inlet	mm O.D.	22			
		Outlet	mm O.D.	22			
	Field pipe size	Inlet	mm I.D.	20			
		Outlet	mm I.D.	20			
Field drain pipe size		mm (in.)	O.D.32 (1-1/4)				
Drawing	External		KL94T470, KL94R952				
	Wiring		KL94R951				
	Refrigerant cycle		-				
Standard attachment	Document		Installation Manual, Instruction Book				
	Accessory		Washer, Drain hose, Tie band, Leg, Screw				
Remarks			* Details on foundation work, duct work, insulation work, electrical wiring, power source switch, and other items shall be referred to the Installation Manual. * Due to continuing improvement, above specifications may be subject to change without notice.				

Notes:		Unit converter
1.Nominal cooling conditions Indoor: 27°C D.B./19°C W.B. (81°F D.B./66°F W.B.), Outdoor: 35°C D.B. (95°F D.B.) Pipe length: 7.5 m (24-9/16 ft.), Level difference: 0 m (0 ft.)		BTU/h =kW x 3,412
2.The values are measured at the factory setting of external static pressure.		cfm =m ³ /min x 35.31
3.Nominal heating conditions Indoor: 20°C D.B. (68°F D.B.), Outdoor: 7°C D.B./6°C W.B. (45°F D.B./43°F W.B.) Pipe length: 7.5 m (24-9/16 ft.), Level difference: 0 m (0 ft.)		lbs =kg/0.4536
4.The values in () show the height of unit with leg.		
5.The factory setting of external static pressure is shown without < > . Refer to "Fan characteristics curves", according to the external static pressure, in DATA BOOK for the usable range of air flow rate.		
6.Be sure to install a valve on the water inlet/outlet.		
7.Install a strainer (40 mesh or more) on the pipe next to the valve to remove the foreign matters.		
8.Please group units that operate on 1 branch of HBC.		
		*Above specification data is subject to rounding variation.