

## LossnayPro LGH-50RVS

An in-ceiling balanced pressure sensible heat recovery ventilation unit featuring a non-permeable counter flow type plastic core. The system can achieve a high thermal exchange efficiency of up to 93%\* and extract from high moisture areas.

Calculation of product embodied carbon under TM65 ANZ local Addendum by CIBSE.




Embodied Carbon Result with 'Mid-level TM65 Calculation' Method Total:

**398 (kg CO<sub>2</sub>e)**


Assessment Date:  
**27<sup>th</sup> September 2023**  
 Assessor / Organisation:  
**Mitsubishi Electric**  
 Contact:  
**compliance@bdt.co.nz**  
 Valid Country:  
**New Zealand**

PRODUCT INFORMATION	
Type of product	MVHR
Equipment capacity	139 L/s
Product weight	55.0kg
Material breakdown for at least 95% of product weight	Yes
Product service life	15 years
Type of refrigerant	N/A
Refrigerant charge	0kg
Country of origin	Japan
Product complexity	Category 3: High



\*Efficiency achieved at fan speed 1.

## Results Breakdown - Embodied Carbon A1 – C4 (Excluding B1 and C1)



## Summary of Embodied Carbon Results (kg CO<sub>2</sub>e)

A1 – C4 (Excluding B1 and C1)	307
A1 – C4 with Buffer Factor (Excluding B1 and C1)	398
B1: Refrigerant Leakage During Life + C1: Refrigerant Leakage at End of Life	0

## Calculation Assumptions

A1: Material Carbon Coefficient Source	TM65 ANZ Local Addendum
A4: Transport to site distances	10,000km by sea, 300km by road (TM65 ANZ assumption)
C4: Percentage of unit being recycled	70% (TM65 ANZ assumption)

Note: Data is correct at time of document publication and may be subject to vary based on manufacturing and shipping variations on a case by case basis.

For more information please visit our website  
or call our Applied Products Team.  
[www.mitsubishi-electric.co.nz](http://www.mitsubishi-electric.co.nz) | 0800 784 382

PUBLISHED JAN 2024

 PLEASE LOOK AFTER THE ENVIRONMENT AND RECYCLE