



Vertical Lossnay VL-250

A balanced pressure heat recovery ventilation unit that can be installed below-ceiling. Featuring a non-permeable, counter flow type resin core, the system can achieve high thermal efficiency of up to 90%* and extract from humid areas.

Calculation of product embodied carbon under TM65 ANZ local Addendum by CIBSE.




Embodied Carbon Result with 'Mid-level TM65 Calculation' Method Total:

198 (kg CO₂e)


Assessment Date:
27th September 2023
 Assessor / Organisation:
Mitsubishi Electric
 Contact:
compliance@bdt.co.nz
 Valid Country:
New Zealand

PRODUCT INFORMATION	
Type of product	MVHR
Equipment capacity	69 L/s
Product weight	26.0kg
Material breakdown for at least 95% of product weight	Yes
Product service life	15 years
Type of refrigerant	N/A
Refrigerant charge	0kg
Country of origin	Japan
Product complexity	Category 3: High



*Efficiency achieved at fan speed 1.

Results Breakdown - Embodied Carbon A1 – C4 (Excluding B1 and C1)



Summary of Embodied Carbon Results (kg CO₂e)

A1 – C4 (Excluding B1 and C1)	152
A1 – C4 with Buffer Factor (Excluding B1 and C1)	198
B1: Refrigerant Leakage During Life + C1: Refrigerant Leakage at End of Life	0

Calculation Assumptions

A1: Material Carbon Coefficient Source	TM65 ANZ Local Addendum
A4: Transport to site distances	10,000km by sea, 300km by road (TM65 ANZ assumption)
C4: Percentage of unit being recycled	70% (TM65 ANZ assumption)

Note: Data is correct at time of document publication and may be subject to vary based on manufacturing and shipping variations on a case by case basis.

For more information please visit our website
or call our Specialist Team.
www.mitsubishi-electric.co.nz | 0800 784 382

PUBLISHED JAN 2024

 PLEASE LOOK AFTER THE ENVIRONMENT AND RECYCLE