

## 2. Specifications

| Model      | Rated Voltage (V) | Frequency (Hz) | Notch | Rated Current (A) | Power consumption (W) | Airflow rate (m <sup>3</sup> /h) | Noise level (dB) | Connecting duct diameter (mm) | Weight (kg) |
|------------|-------------------|----------------|-------|-------------------|-----------------------|----------------------------------|------------------|-------------------------------|-------------|
| V-15ZMW-E  | 220               | 50             | High  | 0.11              | 25                    | 210                              | 21.5             | φ100                          | 6.0         |
|            |                   |                | Low   | 0.10              | 16                    | 145                              | 17.0             |                               |             |
|            | 240               | 50             | High  | 0.12              | 29                    | 215                              | 22.5             |                               |             |
|            |                   |                | Low   | 0.11              | 19                    | 170                              | 19.0             |                               |             |
| V-15ZMWP-E | 220               | 50             | High  | 0.21              | 43                    | 335                              | 26.5             | φ150                          | 6.0         |
|            |                   |                | Low   | 0.18              | 29                    | 275                              | 23.0             |                               |             |
|            | 240               | 50             | High  | 0.22              | 49                    | 350                              | 29.0             |                               |             |
|            |                   |                | Low   | 0.19              | 35                    | 305                              | 26.5             |                               |             |
| V-18ZMW-E  | 220               | 50             | High  | 0.28              | 60                    | 510                              | 31.0             | φ150                          | 8.5         |
|            |                   |                | Low   | 0.24              | 34                    | 370                              | 26.0             |                               |             |
|            | 240               | 50             | High  | 0.28              | 67                    | 520                              | 32.5             |                               |             |
|            |                   |                | Low   | 0.24              | 39                    | 400                              | 28.0             |                               |             |
| V-18ZMWP-E | 220               | 50             | High  | 0.47              | 99                    | 770                              | 32.5             | φ200                          | 9.5         |
|            |                   |                | Low   | 0.45              | 78                    | 650                              | 30.0             |                               |             |
|            | 240               | 50             | High  | 0.47              | 109                   | 780                              | 33.0             |                               |             |
|            |                   |                | Low   | 0.46              | 88                    | 700                              | 32.0             |                               |             |

\* The values are measured using the orifice chamber method.

The noise values are A-scale values measured at a distance of 1.5 m from the side of the machine body for the casing side noise level with the duct attached at the outlet side and intake side.